

485 Optical Touch Module



Overview

Self-testing after booting function. RS485 communication interface with Modbus protocol. Built in 16MB external flash memory to store the font and Object Dictionary Data. Support projected capacitive touch screen (PCAP). Easy-to-use product which allows customers to develop projects rapidly in a very cost-effective way. Mouser offers inventory, pricing, & datasheets for RS-485 Display Modules. Build in buzzer and can be controlled by. WINSTAR Smart Display RS485 Series offers an out-of-the-box Modbus development experience to you, providing below benefits to lower your development costs and speed up your time-to-market expectations. 0" Smart TFT Module is designed for industrial embedded systems. It uses the STM32F767 high-performance microcontroller as the core driver and is paired with an 800×480 resolution IPS LCD panel to present clear picture quality with 16. 7M colors and NTSC 50% color gamut.

Article Content

5 Inch TFT LCD Display with STM32 | Capacitive Touch

Its modular architecture allows developers to quickly integrate touch functions, adjust glass thickness or customize communication protocols, providing cost-effective

6GK1503-2CB00 SIEMENS PROFIBUS OLM/G11 V4.0

Buy 6GK1503-2CB00 SIEMENS PROFIBUS OLM/G11 V4.0 optical link module with 1 RS 485 and 1 glass fiber optic cable interface (2 BFOC sockets), with signaling

RL0F00050000FGDABSA00

5-inch RS485 Modbus Smart TFT Display with Capacitive Touchscreen Model No. RL0F00050000FGDABSA00 ★5 Inch RS485 Smart Display Features: 1.DC 5V

RS485 Modbus Smart LCD Display, Display RS485,

WINSTAR Smart Display products are designed with ST controller which supports ST development tools like TouchGFX and STM32CubeIDE. You can also use ST

TFT Display mit RS485 Schnittstelle von DISPLAY VISIONS GmbH

Tft Rs485, DISPLAY VISIONS bietet ein TFT Display mit RS485 Schnittstelle an. Der Typ EA eDIPTFT43-A hat neben der RS485 Schnittstelle auch noch eine I2C-Bus und eine SPI Schnittstelle

RS485 Modbus Smart LCD Display, Display RS485,

4.IPS TFT display with wider viewing angle optional. Speed time-to-market by using Smart Display 485 TFT Series And what happens when you don't? W/O Using

Setting Up Linux RS-485 Display Module Connectivity

Setting Up Linux RS-485 Display Module Connectivity G2C1 Display Modules have two RS-485 ports, one port on J11 and the second port on J7. These may be

Arduino Opta RS485 - Industrial Micro-PLC with RS

Arduino Opta RS485 is a secure, user-friendly micro PLC featuring Industrial IoT capabilities and robust RS485 communication for reliable automation solutions.

What is RS-485 & How to Use MAX485 with Arduino for

Learn about the industry-favorite RS-485 (EIA-485) wired communication interface standard and learn how to interface the MAX485 module

IRIS RS-485

IRIS RS-485 Mit dem IRIS I/O Modul bieten wir ein industrietaugliches Funkmodul für die Überwachung und Steuerung von Maschinen an. Die IRIS-I/O

RL0F00043000WGDAASA00

5 pport projected capacitive touch screen (PCAP). 6.Embedded buzzer controlled by Master Device. 7 mo set HOST can be used on multiple platforms, such as

1756-UM532A-EN-P, ControlLogix DH-485 Communication Module

Refer to Appendix B, Troubleshoot the 1756-DH485 Module and publication 1756-IN587, the ControlLogix DH-485 Communications Module Installation Instructions, for more information about

Brilliant HMI Display with Modbus Wi-Fi, LAN with touch

Add-on HMI display with touch for all types of PLC control systems. Also with Modbus RTU/TCP. For direct connection in the wall housing. Interface options

RL0F0007000A8GDAASA00

RL0F0007000A8GDAASA00 is integrated with a standard TFT module RFH70BA8-AYW-LNG and 4-layer PCBA with built-in firmware. This 7" Smart Display

5.0" Smart TFT Display with CTP and RS485 (Modbus)

5.0" Smart Display with RS485 interface. Easy-to-use product which allows customers to develop projects rapidly in a very cost-effective way. Designed with

RS-485 display, RS-485 display module

Find your rs-485 display easily amongst the 208 products from the leading brands (FUJI, Winmate, Panasonic Fire & Security, ...) on DirectIndustry, the industry specialist for your professional purchases.

RL0F00035000XGDAASA00

Der Host kann auf mehreren Plattformen verwendet werden, z. B. Computer (mit USB-zu-RS-485-Adapter) oder MCU. Bei Fragen zu RL0F00035000XGDAASA00 wenden Sie sich gerne an unser

RS-485 I/O Modules

RS-485 remote I/O modules support Modbus RTU, CANbus, Profibus, CC-Link, and more for long-distance, noise-resistant communication. Ideal for power

SmartReader™ Multimode

Monochromator-based system for UV through visible absorbance Filter module system for fluorescence assays Advanced PMT detector for luminescence assays

UT-277SM RS-232/485/422 Fiber Optic MODEM -UOTEK

UT-277SM fiber optic modem supports asynchronous RS-232/485/422 communication. It is the best choice to connect remote terminal unit (RTU) with

5 inch Smart TFT LCD Display Module With RS485 Interface

Features: • Act as master in Modbus communication, suitable for industry control application • Wide operating voltage • Upgradable through PC or USB OTG • Stable and reliable resistive touch • Smart

RS-485 I/O Modules: ADAM-4000/4100

Cost-effective remote RS-485 data acquisition modules offer analog, RTD, thermocouple, digital, relay and counter I/O with Modbus RTU protocol.

TFT Display mit RS485 Schnittstelle von DISPLAY VISIONS GmbH

Über einen externen Baustein SN75176 kann dieses TFT Display auch direkt an ein RS485 Schnittstelle angebunden werden. Es können auch mehrere Displays über die RS485 angeschlossen werden.

3.5-inch RS485 Modbus Smart TFT Display with

This 3.5" RS485 series TFT is an easy-to-use product that allows you to develop projects rapidly in a cost-effective way. WINSTAR's RS485 Smart Display Series

Contact Us

For more information, pricing, or custom solutions, please contact us:

Website: <https://www.aitaf.it>

Email: info@aitaf.it

Phone: +39 331 847 2365

Address: Via Raffaello Sanzio 11, 20149 Milan, Italy

This document is for informational purposes only. Specifications subject to change without notice.

